

INOLINE




IMPORTANT SAFEGUARDS AND WARNINGS

- This is a quick guide which MUST first be read and understood before using this securement system.
- J-Hooks must be attached to a solid wheelchair frame (no spokes, wheels or movable components).
- Shoulder and Lap Belt (we recommend using both) MUST go across occupant's shoulder and hip, and not be held away from the occupant's body by wheelchair components.

SECURING WHEELCHAIR



- 1. Wheelchair behind ramp.
- Lock brakes or power off chair.
- **3.** Press and hold both buttons (4 sec) to release front retractors.



RELEASING WHEELCHAIR



- 1. Unbuckle shoulder and lap belt (place in storage).
- **2.** Unlock brakes and keep chair powered off.






- **4.** Attach front J-Hooks to solid frame (30 sec).
- 5. Unlock brakes and keep chair powered off.
- 6. Press and hold Z Button.
- 7. Push Thumb Controller forward—moves chair up ramp.
- CAUTION: Move Controller left or right to adjust chair's direction.



- **3.** Press and hold Unlock Button (4 sec) to release retractors.
- 4. Press lever on retractors.
- 5. Detach rear J-Hooks.
- Remove retractors from floor and place in storage.






- 9. Release Z Button and place Controller in storage.
- 10. Attach rear retractors to floor.
- Attach J-Hooks to solid frame.
- 12. Press and hold Lock Button (3 sec) to lock retractors.





- 7. Press and hold Z Button.
- 8: Push Thumb Controller downward; moves chair down ramp.
- **9. CAUTION:** Move Controller left or right to adjust chair's direction.
- **10.** Release Z Button and place Controller in storage.
- Lock brakes and keep chair powered off.






- **13.** Buckle shoulder and lap belt in place.
- **14.** Lock brakes and keep chair powered off, ready for transport.





- **12.** Press and hold both buttons (4 sec) to release retractors.
- Return J-Hooks to stowage.
- **14.** Unlock brakes or power on chair.
- 15. Place chair in secure area.



Ocontact a Q'Straint® Authorized Dealer or Customer Service (800) 987-9987. www.qstraint.com

These instructions contain the most current information at the time of printing. Q'Straint® reserves the right to alter or modify contents and/or components without notice.

© 2017 Q'Straint®. All Rights Reserved.

QC17007 Rev A